

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE
Product code : 000000000001512854
Chemical nature : Molybdenum disulfide grease

Manufacturer or supplier's details

Company : Dow Corning (Zhangjiagang) Holding Company Limited
Address : **18 Beihai Road, Yangtze River International Chemical Industry Park, Zhangjiagang, Jiangsu Province, P.R.C., Postal Code: 215634**
Telephone : 400 880 7110
Emergency telephone number : **(86 512) 56732049**
E-mail address : **China.info@dowcorning.com**

Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance : Grease
Colour : black
Odour : slight

Causes mild skin irritation. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

GHS Classification

Skin corrosion/irritation : Category 3
Serious eye damage/eye irritation : Category 1
Acute aquatic toxicity : Category 3
Chronic aquatic toxicity : Category 3

GHS label elements

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H316 Causes mild skin irritation.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Physical and chemical hazards

Not classified based on available information.

Health hazards

Causes mild skin irritation. Causes serious eye damage.

Environmental hazards

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 -< 50
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>= 30 -< 50
12-Hydroxy lithium stearate	7620-77-1	>= 1 -< 10
Residual oils (petroleum), solvent-dewaxed	64742-62-7	>= 1 -< 10

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	>= 3 -< 10
Graphite	7782-42-5	>= 1 -< 10
Lithium hydroxide	1310-65-2	>= 0.1 -< 0.25

4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes mild skin irritation.
Causes serious eye damage.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire- : Exposure to combustion products may be a hazard to health.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 2017/03/18
2.3	2017/09/14	825962-00010	Date of first issue: 2014/11/25

fighting

Hazardous combustion products : Carbon oxides
Metal oxides
Oxides of phosphorus
Sulphur oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Advice on safe handling : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : Keep in properly labelled containers.
Keep tightly closed.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

Packaging material : Unsuitable material: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Inhalable fraction)	5 mg/m ³	ACGIH
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Inhalable fraction)	5 mg/m ³	ACGIH
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m ³	ACGIH
Residual oils (petroleum), solvent-dewaxed	64742-62-7	TWA (Inhalable fraction)	5 mg/m ³	ACGIH
Graphite	7782-42-5	PC-TWA (Total dust)	4 mg/m ³	GBZ 2.1-2007
		PC-TWA (Respirable dust)	2 mg/m ³	GBZ 2.1-2007
		TWA (Respirable fraction)	2 mg/m ³	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3	Revision Date: 2017/09/14	SDS Number: 825962-00010	Date of last issue: 2017/03/18 Date of first issue: 2014/11/25
----------------	------------------------------	-----------------------------	---

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type

Eye/face protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Grease

Colour : black

Odour : slight

Odour Threshold : No data available

pH : Not applicable

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : > 200 °C
Method: closed cup

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : Not applicable

Relative vapour density : No data available

Relative density : 0.89

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Exposure routes : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 10 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Residual oils (petroleum), solvent-dewaxed:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 hrs
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 3,600 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Graphite:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3	Revision Date: 2017/09/14	SDS Number: 825962-00010	Date of last issue: 2017/03/18 Date of first issue: 2014/11/25
----------------	------------------------------	-----------------------------	---

Lithium hydroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute inhalation toxicity : LC50 (Rat): > 3.4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Causes mild skin irritation.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit
Result: No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Species: Rabbit
Result: Skin irritation

Graphite:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 2017/03/18
2.3	2017/09/14	825962-00010	Date of first issue: 2014/11/25

Lithium hydroxide:

Method: In Vitro Membrane Barrier Test Method for Skin Corrosion - CORROSITEX
Result: Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit
Result: No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Species: Rabbit
Result: Irreversible effects on the eye

Graphite:

Species: Rabbit
Result: No eye irritation

Lithium hydroxide:

Result: Irreversible effects on the eye
Remarks: Based on skin corrosivity.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3	Revision Date: 2017/09/14	SDS Number: 825962-00010	Date of last issue: 2017/03/18 Date of first issue: 2014/11/25
----------------	------------------------------	-----------------------------	---

Respiratory sensitisation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Test Type: Local lymph node assay (LLNA)
Exposure routes: Skin contact
Species: Mouse
Method: OECD Test Guideline 429
Result: negative

Residual oils (petroleum), solvent-dewaxed:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

Graphite:

Test Type: Local lymph node assay (LLNA)
Exposure routes: Skin contact
Species: Mouse
Result: negative

Lithium hydroxide:

Test Type: Buehler Test

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Lithium hydroxide:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version
2.3

Revision Date:
2017/09/14

SDS Number:
825962-00010

Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Residual oils (petroleum), solvent-dewaxed:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Result: negative

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Lithium hydroxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

12-Hydroxy lithium stearate:

Exposure routes: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 2017/03/18
2.3	2017/09/14	825962-00010	Date of first issue: 2014/11/25

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rat
NOAEL: > 0.98 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 Days

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 4 Weeks
Method: OECD Test Guideline 410
Remarks: Based on data from similar materials

Species: Rat
NOAEL: > 980 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Species: Rat
NOAEL: > 88 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Residual oils (petroleum), solvent-dewaxed:

Species: Rat
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks
Method: OECD Test Guideline 411
Remarks: Based on data from similar materials

Species: Rat
NOAEL: > 980 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Remarks: Based on data from similar materials

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Species: Rat
NOAEL: 160 mg/kg
Application Route: Ingestion

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3	Revision Date: 2017/09/14	SDS Number: 825962-00010	Date of last issue: 2017/03/18 Date of first issue: 2014/11/25
----------------	------------------------------	-----------------------------	---

Exposure time: 28 - 40 Days
Method: OECD Test Guideline 422

Graphite:

Species: Rat
NOAEL: 12 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 Days
Method: OECD Test Guideline 412

Lithium hydroxide:

Species: Rat
NOAEL: 48 mg/kg
LOAEL: 120 mg/kg
Application Route: Ingestion
Exposure time: 2 yr

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
aquatic invertebrates : Exposure time: 48 h
Test substance: Water Accommodated Fraction

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

Toxicity to microorganisms : NOEC: \geq 1.93 mg/l
Exposure time: 10 min

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Residual oils (petroleum), solvent-dewaxed:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): 4.5 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 23 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): 24 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.4 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Graphite:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Lithium hydroxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 62.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 34.3 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 87.57 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 5.71 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 9.9 mg/l
Exposure time: 34 d

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2.3 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50: 180.8 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Residual oils (petroleum), solvent-dewaxed:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3 Revision Date: 2017/09/14 SDS Number: 825962-00010 Date of last issue: 2017/03/18
Date of first issue: 2014/11/25

Bioaccumulative potential

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Partition coefficient: n-octanol/water : log Pow: 0.69

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

Not regulated as a dangerous good

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

The components of this product are reported in the following inventories:

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version 2.3	Revision Date: 2017/09/14	SDS Number: 825962-00010	Date of last issue: 2017/03/18 Date of first issue: 2014/11/25
----------------	------------------------------	-----------------------------	---

NZIoC	:	All ingredients listed or exempt.
REACH	:	For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
TSCA	:	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
PICCS	:	All ingredients listed or exempt.
KECI	:	All ingredients listed, exempt or notified.
IECSC	:	All ingredients listed or exempt.
AICS	:	All ingredients listed or exempt.
DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
ENCS/ISHL	:	All components are listed on ENCS/ISHL or exempted from inventory listing.
TCSI	:	All ingredients listed or exempt.

16. OTHER INFORMATION

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
GBZ 2.1-2007 : Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average
GBZ 2.1-2007 / PC-TWA : Permissible concentration - time weighted average

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519

DOW CORNING

MOLYKOTE(R) BR-2 PLUS HIGH PERFORMANCE GREASE

Version	Revision Date:	SDS Number:	Date of last issue: 2017/03/18
2.3	2017/09/14	825962-00010	Date of first issue: 2014/11/25

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CN / EN